Farm fence material-Factory wholesale









Farm fence fabric is made from high-purity imported PVC base fabric, laminated or knife-coated to offer excellent airtightness, durability, and UV resistance. It is used to make farm fences, providing a quick and economical solution. The fabric is suitable for large agricultural, livestock, and aquaculture buildings, as well as for roofs of large livestock activity areas and riding halls.

Professional sales team, over 15 years experience in producing PVC membrane structure tensile fabric, Over 10 years OEM&ODM finished product experience, we are a factory produces pvc tarpulinin Haining, The greatest feature of our PVC membrane structure tensile fabric is stable and durable quality.





Welcome to OURFACTORY





You can get the reasonable price with best quality here.







Corrosion resistance:

As a professional PVC tarpaulin manufacturer, the production of gs PVC material is industry leading, because our equipment is imported from Germany, research and development technology team is also from Germany, the advanced production support can ensure that PVC material are corrosion resistant, with more than 10 years.

UV risistant:

The GSTRP PVC tarps are all UV-protected, which is a very important feature for it, by taking into account the surface and coating, it consists of a 6-layer barrier against UV rays.

Heat insulation:

The PVC coated fabic is formulated so that the coating is flame retardant, an extra layer of security is added to protect against sub–ultraviolet rays, and has good insulation against heat sources.

Scratch resistant:

The PVC coated fabic is a kind of liquid PVC uniformly coated on top of the base cloth, the upper and lower two two surfaces are smooth and strong, and polyester base cloth on the high strength, can prevent sharp objects scratch or puncture, with good scratch resistance.

Anti-static

fabri is completely anti-static, this is very important for safety, all purchasing German production equipment, anti-static level is 10E7.






			450gsm	500gsm	550gsm	900gsm
Properties	Units	Test method	Average value	Average value	Average value	Average value
Base Thread Density	Denier	DIN53350	500D*500D	1000D*1000D	1000D*1000D	1000D*1000D
Base Fabric Density	Thread/inch	DIN53351	18*16	20*20	18*18	28*26
Finished Fabric Weight	Gram/m2	DIN53352	580	500	550	900
Base Fabric Weight	Gram/m2	DIN53352	95	172	157	236
Thickness – finished product	um	DIN53352	54	40	42	72
Break Strength Warp	N/5cm	GB/T1040	1500	2000	2000	3500
Break Strength Weft	N/5cm	GB/T1040	1200	1800	1800	3300
Tear Strength Warp	N/5cm	DIN 53363	250	250	220	500
Tear Strength Weft	N/5cm	DIN 53363	200	220	200	450
Adhension	N/5cm	DIN 53357	50	120	120	120
Temperature range	$^{\circ}$	DIN 53368	-30~+70°C	–30~+70°C	-30~+70°C	- 30~+70℃
Fire Retardant		Self- extinguishing				Top side

Multiple colors













Farm fence material-Factory wholesale





















Jiaxing Green Shield New Materials Co., Ltd

Mobile: 0086 13625863196 WhatsApp: 0086 13625863196

Add: No.365 West Qianjiang Road, Haining, Zhejiang, China
e-mail: bill@gstarp.com