





**PVC** breed tarpaulin is a high-strengh pvc coated or laminated polyerter fabric which used to build modern farms with waterproof, durable, convenient and corrosion-resistant properties. Also it can be used to make the shed cover of the breeding shed, as well as mobile breeding shed, providing protection against rain, wind and sun. And it is used to make manure conveyor belt to ensure timely handling of manure to provide cleanliness, as a fencing material to protect against the external environment, PVC water pipe provides pressure and leakage resistance, is lightweight, fast and very durable. This material can withstand extreme environments, is economical and practical, and improves overall farming efficiency and environmental hygiene.

## tarpaulin Available Worldwide



## **breed tarpaulin Available Worldwide**

GSTAPP

**GSTRP** is a professional factory produces PVC breed tarpaulin with over 15 years of experience. Our products are sold to more than 150 countries around the world. We can produce PVC breed tarpaulin with weights ranging from 650g to 2700g, with a maximum width of 5.1 meters. We can produce any color according to RAL, PANTONE, or sample. Width and length can also be made according to customer requirements.







WEB: www.gstarp.com



Jiaxing Green Shield New Materials Co., Ltd





Professional sales team, Over 10 years OEM&ODM finished product experience, Gemeny production lines, Automatic computer colour meching system, Advanced inspection process, Imported pvc resin, Can deliver what exactly client need.



## **Environmental Adaptability:**

We have exported a lot ofproducts to Southeast Asia, Middle East, North America and other regions of the customer, have good reputations, also the product environmental adaptability is very good, its work temperature is from – 40–70.







## Price Advantage:

We are a manufacturer, as a maker, we have the advanced production line imported from Germany, the products are stable and at the same time have the cost advantage, so the price is very competitive.




**Printable:** The fabic has the feature of printable, making it widely used in advertising industry, it can print LOGO according to customer's requirements.











**Color fastness:** Imported pigments are added for sg fabric in the production process, with anti–UV additives, it forms a stable polymer compounds, can maintain this color, and will not fade in the direct light of the eye and hot and humid environment for a long time.



**Safety:** Corrosion resistance, no harmful substances, very small deformation rate, anti–static, flame retardant heat insulation, very safe.





			650sm	850gsm	900gsm	1050sm	1100gsm	1250gsm	1350gsm
Properties	Units	Test method	Average value	Average value	Average value	Average value	Average value	Average value	Average value
Base Thread Density	Denier	DIN53350	1000D*1000D	500D*500D	1000D*1000D	1000D*1000D	1300D*1300D	1500D*1500D	1500D*1500D
Base Fabric Density	Thread/inch	DIN53351	20*20	18*17	28*26	30*30 Panama	30*30 Panama	30*30 Panama	30*30 Panama
Finished Fabric Weight	Gram/m <sup>2</sup>	DIN53352	650	850	900	1050	1100	1250	1350
Base Fabric Weight	Gram/m <sup>2</sup>	DIN53352	175	75	236	265	320	380	380
Thickness – finished product	um	DIN53352	52	65	72	80	88	100	106
Break Strength Warp	N/5cm	GB/T1040	2500	1250	3500	4200	5500	7000	7000
Break Strength Weft	N/5cm	GB/T1040	2200	1150	3300	4000	5000	6800	6800
Tear Strength Warp	N/5cm	DIN 53363	280	150	500	600	700	1000	1000
Tear Strength Weft	N/5cm	DIN 53363	250	125	450	550	700	900	900
Adhension	N/5cm	DIN 53357	90	100	120	120	120	120	120
Temperature range	${\mathbb C}$	DIN 53368	-30~+70°C	-30~+70°C	-30~+70°C	-30~+70℃	-30~+70°C	-30~+70℃	A Grade
Flame retardancy		Self- extinguishing			Top side	Both sides lacquring	TRIPLE LACQURING		PVDF(unweldable) /PVDF(weldable)

Jiaxing Green Shield New Materials Co., Ltd

Mobile: 0086 13625863196 WhatsApp: 0086 13625863196

Add: No.365 West Qianjiang Road, Haining, Zhejiang, China

e-mail: bill@gstarp.com WEB: www.gstarp.com