

PVC car wash mats and garage protect mats are made of highstrength PVC waterproof material, it's a heavyduty pvc tarpaulin. PVC car wash mats is used to prevent sewage from flowing around and polluting the ground when washing a car, and also it can be used to protect the garage floor from rain and snow. The car wash mats have inflatable structures with high surrounding edges, effectively preventing the spread of water, dirt, mud, snow and detergents, keeping the surroundings tidy. This material has excellent waterproof and snowmelt resistance, easy to clean and durable. Its wear–resistant, non–slip performance ensures long service life, is the ideal material for home and commercial places, especially suitable for cold or wet environment, very hot in the United States and Canada, Europe.

Main Products

1 PVC Garage mat

2 car wash mat material

3 car wash curtain material

4 PVC car wash containment mat material

PVC Car wash mats material Available Worldwide

Characteristics of materials



Professional sales team, Over 15 years experience in producing PVC Car wash mat material, Over 10 years OEM&ODM finished product experience, Gemeny production lines, Automatic computer colour meching system, Advanced inspection process, Imported pvc resin, Can deliver what exactly client need.

Scratch resistant:

The PVC coated fabic is a kind of liquid PVC uniformly coated on top of the base cloth, the upper and lower two two surfaces are smooth and strong, and polyester base cloth on the high strength, can prevent sharp objects scratch or puncture, with good scratch resistance.



2

Wear-resistant:

The fabric surface is very smooth, the surface coating is arranged tightly via surface acrylic or PVDF treatment techniques, the hardness is very high, resisting all kinds of wear and tear, so it is very wear–resistant.

3

Smooth surface:

The graphic cloth is made by lamination or coating, and with the special treatment on the surface, the surface is very smooth.

Characteristics of materials





Colors customizable:

We can make any colors as customers's samples or Pantone colors number or RAL color number, we have automatic color matching equipment, manually matching the color is not needed, which is our advantages.




Anti-static:

fabri is completely anti–static, this is very important for safety, all purchasing German production equipment, anti-static level is 10E7.



Long lifetime:

Produced by coating or coating process, the product structure is stable, quality is stable, with strong durability, to ensure economic returns, the product has a very good service life, over 10 years






No odor













			680gsm	750gsm	800gsm
Properties	Units	Test method	Average value	Average value	Average value
Base Thread Density	Denier	DIN53350	1000D*1000D Low–wick	1000D*1000D	1000D*1000D
Base Fabric Density	Thread/inch	DIN53351	20 *20	23*23	23*23
Finished Fabric Weight	Gram/m²	DIN53352	680	750	800
Base Fabric Weight	Gram/m ²	DIN53352	175	200	200
Thickness – finished product	um	DIN53352	52	60	62
Break Strength Warp	N/5cm	GB/T1040	2500	3000	3000
Break Strength Weft	N/5cm	GB/T1040	2200	2800	2800
Tear Strength Warp	N/5cm	DIN 53363	280	300	300
Tear Strength Weft	N/5cm	DIN 53363	250	270	270
Adhension	N/5cm	DIN 53357	90	120	120
Temperature range	${\mathbb C}$	DIN 53368	–30~+70°C	–30~+70°C	–30~+70°C
Flame retardancy		Self- extinguishing	Both sides lacquring	Both sides lacquring	Embossing

Jiaxing Green Shield New Materials Co., Ltd

Mobile: 0086 13625863196 WhatsApp: 0086 13625863196

Add: No.365 West Qianjiang Road, Haining, Zhejiang, China

e-mail: bill@gstarp.com