side curtain fabric –Factory wholesale



PVC side curtain fabric is a high–strength pvc coated fabric, mainly used in the production of pvc truck side curtain fabric, high–density substrate and PVC coating to provide high strength, the most popular gram weight is between 610–1250gsm, many customers choose 610 and 650 grams of fabric. It can be applied to container transportation/train transportation/truck transportation/production plant/storage and other fields, the color can be customized with better ink absorption performance. It can meet the printing requirements of customers, printing a variety of large or small patterns, suitable for a variety of enterprises /warehouses/brand publicity, our maximum width is 5.1 meters, the surface is specially treated, very soft. Good hand feeling, very flexible, strong toughness, easy to disassemble and install, easy to clean, and good self–cleaning performance. UV resistant function, durable, long service cycle, excellent physical properties, common in daily life, industrial production and other fields.



Wight:

610gsm

650gsm

680gsm

700gsm

850gsm

900gsm

1050gsm

1100gsm

Customization is also possible


side curtain fabric – Factory wholesale



Anti-bacterial and anti-mildew Through special chemical additives, it can ensure that all our products have good anti-bacterial and anti-mildew effect, which will not produce mold in a humid and warm environment, maintain the stability of the surface, will not produce unpleasant odor with long service life.









Features:

- ▶ The most popular weight is 610–1250gsm
- ▶ used for various transportation/production factory/storage fields
- with better absorption performance
- meeting customer printing requirements
- ▶ suitable for various enterprises/warehouses/brand promotion
- good hand feel / strong toughness
- easy to disassemble and install easy to clean
- ▶ with good self-cleaning performance
- ▶ anti-ultraviolet durable
- ▶ long life, excellent physical properties
- antibacterial and anti-mildew



100% waterproof




Superior UV Protection




side curtain fabric – Factory wholesale



Common Weights for PVC Side Curtain Fabric:









Can PVC Side Curtain Fabric Be Printed?

Yes, PVC Side Curtain Fabric can be printed. Common printing methods include:

Digital printing is typically used for complex, multi-colored patterns with high precision, ideal for brand promotion and advertising. Screen printing is suitable for single-color designs and large-scale production at low costs.




- Heat transfer printing is used for custom designs, offering bright colors that last long without fading, making it ideal for small-scale production.
- Printing advertisements on PVC Side Curtain Fabric can generate good economic benefits for business owners and enhance the aesthetics of vehicles, adding a visual appeal to long-distance transportation.





Proper Use of PVC Side Curtain Fabric:

Avoid sharp edges that could cause damage during use. If any damage occurs, repair it promptly. Ensure the dimensions match the vehicle during installation, similar to how a car cover is installed. Avoid overstretching the fabric while ensuring a snug fit.

















| Items | polyester fabric | weight(g/sqm) | Description | | |
|----------|-------------------------|---------------|-------------------------|--|--|
| GLT1101 | 1000D*1000D 30*30 | 750 | | | |
| GLT1102 | 1000D*1000D 20*20 | 680 | PVC laminated tarpaulin | | |
| GLT1103 | 1000D*1000D 20*20 | 650 | | | |
| GCT2201 | 1000D*1000D 30*30 | 1050 | | | |
| GCT2202 | 1000D*1000D 30*30 | 900 | | | |
| GCT2203 | 1000D*1000D 23*23 | 850 | | | |
| GCT2204 | 1000D*1000D 23*23 | 750 | PVC coated tarpaulin | | |
| GCT2205 | 1000D*1000D 20*20 | 680 | | | |
| GCT2206 | 1000D*1000D 20*20 | 650 | | | |
| GCT2207 | 1000D*1000D 20*20 | 700 | | | |
| GKCT3301 | 1000D*1000D 30*30Panama | 1350 | | | |
| GKCT3302 | 1000D*1000D 30*30Panama | 1250 | | | |
| GKCT3303 | 1000D*1000D 30*30Panama | 1050 | Knife coated tarpaulin | | |
| GKCT3304 | 1000D*1000D 23*23 | 850 | | | |
| GKCT3305 | 1000D*1000D 20*20 | 650 | | | |





| | | | 850gsm | 900gsm | 1050gsm | 1250gsm |
|----------------------------|---------------|------------------------|-----------------------|------------------|-------------------------|------------------|
| Properties | Units | Test method | Average value | Average value | Average value | Average value |
| Base Thread Density | Denier | DIN53350 | 1000D*1000D | 1000D*1000D | 1000D*1000D | 1000D*1000D |
| Base Fabric Density | Thread/inch | DIN53351 | 23*23 | 30*30 Panama | 30*30 Panama | 30*30 Panama |
| Finished Fabric Weight | Gram/m2 | DIN53352 | 850 | 900 | 1050 | 1250 |
| Base Fabric Weight | Gram/m2 | DIN53352 | 200 | 265 | 265 | 380 |
| Thickness-finished product | um | DIN53352 | 65 | 75 | 80 | 100 |
| Break Strength Warp | N/5cm | GB/T1040 | 3000 | 4200 | 4200 | 7000 |
| Break Strength Weft | N/5cm | GB/T1040 | 2800 | 4000 | 4000 | 6800 |
| Tear Strength Warp | N/5cm | DIN 53363 | 300 | 600 | 600 | 1000 |
| Tear Strength Weft | N/5cm | DIN 53363 | 270 | 550 | 550 | 900 |
| Adhension | N/5cm | DIN 53357 | 120 | 120 | 120 | 120 |
| Temperature range | ${\mathbb C}$ | DIN 53368 | - 30~+70 | - 40~+70 | -30~+70 | -30~+70 |
| Fire Retardant | | Self- extinguishing | Both sides Acrylic | ACRYLIC | Both sides lacquring | |

Jiaxing Green Shield New Materials Co., Ltd

Mobile: 0086 13625863196 WhatsApp: 0086 13625863196

Add: No.365 West Qianjiang Road, Haining, Zhejiang, China

e-mail: bill@gstarp.com