Safety fence-Factory wholesale





Customization is also possible

Safety fence-Factory wholesale



Scaffolding tarpaulins provide excellent protection for personnel and buildings.

Safety fence tarp is a kind of breathable PVC woven fabric, also called Scaffolding tarpaulins, pvc coated on the base fabric, common in construction sites, protect workplace safety, occupy the majority of the use share, especially suitable for construction sites or other occasions requiring temporary isolation. What distinguishes it lies in high strength, tear resistance, strong tensile ability, strong toughness, resistance to friction/bump/impact/impact resistance. It can adapt to harsh working environment, which is durable and economical.











Safety fence-Factory wholesale



PVC Safety Mesh Fabric is a mesh structure product, which is made of high purity PVC and glue mixed compound in polyester fabric, the substrate features high strength and tear strength, is common in construction sites, protect construction safety, occupy the majority of the use share, especially suitable for construction sites or other temporary isolation occasions. What distinguishes this produces lies in high strength, tear resistance, strong tensile ability.





Applications of Safety Fence Tarpaulin

Construction Sites:

Widely used to enclose construction sites, providing protection for workers' safety and preventing the risk of falling objects or debris. It also helps reduce noise, control dust, and ensures pedestrian safety around the site.

Sports and Large Event Venues:

Temporary fences are erected for crowd control or to conceal activities within the venue, providing security, privacy, and effective segregation of different areas.

Agricultural, Forestry, and Livestock Areas:

Used around farms, forests, and animal husbandry sites to block wind, dust, and protect livestock and crops.

















Safety fence–Factory wholesale







Super Tear Resistance



Good tensile strength







Super strong adhesion



Flame retardant

Safety fence-Specifications



Spec	Properties	Average value
1000D*1000D 12*12	Weight	120g
	Break Strength Warp	1250N/5cm
	Break Strength Weft	1250N/5cm
	Tear Strength Warp	300N
	Tear Strength Weft	310N
	transmittance	37%
	permeability	2711mm/s

Spec	Properties	Average value
500D*500D 18*18	Weight	210 ± 10g
	Break Strength Warp	1273N/5cm
	Break Strength Weft	1074N/5cm
	Tear Strength Warp	187N
	Tear Strength Weft	132N

Spec	Properties	Average value
1000D*1000D 9*9	Weight	240 ± 10g
	Break Strength Warp	946N/5cm
	Break Strength Weft	917N/5cm
	Tear Strength Warp	242N
	Tear Strength Weft	110N

Spec	Properties	Average value
500D*1000D 18*14	Weight	330g
	Break Strength Warp	2377.7N/5cm
	Break Strength Weft	2327.8N/5cm
	Tear Strength Warp	392.7N
	Tear Strength Weft	186.3N

Jiaxing Green Shield New Materials Co., Ltd

Mobile: 0086 13625863196 WhatsApp: 0086 13625863196

Add: No.365 West Qianjiang Road, Haining, Zhejiang, China

e-mail: bill@gstarp.com